

### A621 - Guanto anti taglio in schiuma di nitrile 3/4

**Collezione:** Resistenza al taglio

**Gamma:** Guanti

**Materiali:** HPPE, Poliestere, Fibra di vetro, Elastane

**Immersione:**

**Pacchetto interno:** 12

**Cartone esterno:** 144

### Informazioni prodotto

Suprema resistenza al taglio abbinata ad un eccezionale grip. Immersione 3/4 in schiuma di nitrile contro l'olio per mantenere le mani pulite, asciutte e per garantire una presa sicura.

### Guanti

È disponibile un'ampia e crescente gamma di modelli per la protezione delle mani. Per aiutare a soddisfare ogni esigenza. Nella produzione dell'ampia gamma di modelli per la protezione delle mani di Portwest vengono utilizzati solo i migliori materiali e metodi di fabbricazione....

### Norme

EN ISO 21420 Destrezza 5

EN 388 : 2016+A1: 2018 (4X43D)

EN 407 (X1XXXX)

ANSI/ISEA 105: 2016 Livello TAGLIO (A4)



### Caratteristiche

- Resistenza al taglio di livello D
- Maglia calibro 13 per una perfetta vestibilità
- Rivestimento in schiuma di nitrile per un grip eccellente in condizioni di umido e secco
- Immersione a 3/4 per una maggior protezione
- Super resistenza ad abrasione e strappo
- Protezione contro il calore da contatto fino a 100°C
- Maglia traspirante senza cuciture
- Certificato CE
- Blister che aiuta la presentazione per le vendite al dettaglio
- ANSI Livello al taglio A4
- Marcato UKCA

**A621 - Guanto anti taglio in schiuma di nitrile 3/4****Codice doganale: 6116108091****Laboratorio**

SATRA Technology Europe Ltd (Organismo certificatore n...: NB: 2777)

Bracetown Business Park

D15 YN2P, Ireland

Certificato numero: 2777/18137-01/E00-00

**Carton Dimensions/Weight**

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m <sup>3</sup> )	EAN13	DUN14
A621BKRS	Nero	45.0	37.0	27.0	0.1040	0.0450	5036108228225	15036108716392
A621BKRM	Nero	45.0	37.0	27.0	0.1020	0.0450	5036108201846	15036108690166
A621BKRL	Nero	45.0	37.0	27.0	0.1200	0.0450	5036108201839	15036108690159
A621BKRXL	Nero	45.0	37.0	27.0	0.1300	0.0450	5036108201853	15036108690173
A621BKRXXL	Nero	45.0	37.0	27.0	0.1300	0.0450	5036108246359	15036108734914
A621BKRXXXL	Nero	45.0	37.0	27.0	0.1440	0.0450	5036108292523	15036108782427

### DICHIARAZIONE DI CONFORMITÀ DI TIPO UE REGOLAMENTO (UE) 2016/425 SUI DISPOSITIVI DI PROTEZIONE INDIVIDUALE

Questa dichiarazione di conformità è rilasciata sotto l'esclusiva responsabilità del produttore Portwest, IDA Industrial Park, Westport, Co. Mayo, F28 FY88, Ireland. Reg. 21284 dichiara che i seguenti Dispositivi di Protezione Individuale (DPI)

#### **A621 - GUANTO ANTI TAGLIO IN SCHIUMA DI NITRILE 3/4**



è conforme alle disposizioni del regolamento sui DPI (UE) 2016/425 (Cat II) e soddisfa i requisiti essenziali di salute e sicurezza di cui all'allegato II e le relative norme armonizzate:

EN ISO 21420 Destrezza 5

EN 388 : 2016+A1: 2018 (4X43D)

EN 407 (X1XXXX) (2020)

ANSI/ISEA 105: 2016 Livello TAGLIO (A4) (2016)

Il DPI è identico al modello oggetto del certificato di esame UE del tipo (Modulo B) a cui si fa riferimento nel numero del certificato

**2777/18137-01/E00-00**

Rilasciato da: SATRA Technology Europe Ltd

Bracetown Business Park, Clonee, Dublin 15, D15 YN2P, Ireland (NB: 2777)

Firmato in nome e per conto di Portwest



Raymond Carney

Chief Operations Officer

Data: 24-Jan-2023



Issued to:

Portwest  
IDA Industrial Park  
Westport  
County Mayo  
F28 FY88  
Eire

Notified Body: 2777

SATRA customer number: P0214

# EU Type-Examination Certificate

## Certificate number: 2777/18137-01/E00-00

This EU Type-Examination Certificate covers the following product group(s) supported by testing to the relevant standards/technical specifications and examination of the technical file documentation:

Following the EU Type-Examination this product group has been shown to satisfy the applicable essential health and safety requirements of Annex II of the PPE Regulation (EU) 2016/425 as a Category II product.

**Product reference:**

**Description:**

A621

13G HPPE and glass fibre liner, with foam nitrile coated glove

**Sizes:**

**Classification:**

		<b>EN 388:2016+A1:2018</b>	<b>Level</b>	<b>EN 407:2004</b>	<b>Level</b>
7	S	Abrasion Resistance	4	Burning Behaviour	X
8	M	Blade Cut Resistance	X	Contact Heat	1
9	L	Tear Resistance	4	Convective Heat	X
10	XL	Puncture Resistance	3	Radiant Heat	X
11	XXL	TDM Cut Resistance	D	Small Splashes of Molten Metal	X
				Large Quantities of Molten Metal	X

Standards/Technical specifications applied:  
EN ISO 21420:2020; EN 388:2016+A1:2018; EN 407: 2004

Technical reports/Approval documents:  
CTC: S190201709\_1, S150705019\_2, S160301002\_1, S181115587\_1, S161213448\_1  
Intertek: GZHT90848885(S1)

Signed on behalf of SATRA:

Quincey Brown

**Date first issued:** 20/08/2021  
**Date of issue:** 20/08/2021  
**Expiry date:** 20/08/2026

# TERMS AND CONDITIONS

The following conditions apply in addition to SATRA's standard terms and conditions of business and those given in the current certification agreement. This certificate has been issued in accordance with Annex V (Module B) of the applicable legislation (see note 11).

Please note:

1. Where the product is classified as category III then CE or UKCA Marking of production is reliant on current compliance with module C2 or Module D of the applicable legislation (See note 11). (Except that specifically produced to fit an individual user).
2. Full details of the scope of the certification and product(s) certified are contained within the manufacturer's technical documentation.
3. Where a translation of this certificate exists, the English language version shall be considered as the authoritative text.
4. Certification is limited to production undertaken at the sites listed in the manufacturer's technical documentation.
5. Ongoing manufactured product shall be consistent with the product(s) certified and listed on this certificate and an EU declaration of product conformity shall be made available in accordance with the applicable legislation (See note 11)
6. The Manufacturer shall inform SATRA of any changes to the certified product or technical documentation.
7. Where results obtained during type testing are within the budget of uncertainty when compared to the pass requirement, classification or performance level, then it is the responsibility of the manufacturer to ensure that the factory production control and manufacturing tolerances are such that the product placed on the market meets with the stated requirements, classifications or performance levels.
8. This certificate shall be kept together with the relevant technical documentation in a safe place by the client named on this certificate. Production of this certificate and other documentation may be required by a representative of the EC member state, or UK government.
9. This certificate relates only to the condition of the testable items at the time of the certification procedure and is subject to the expiry date shown.
10. SATRA reserves the right to withdraw this certificate if it is found that a condition of manufacture, design, materials or packaging have been changed and therefore no longer comply with the requirements of the applicable legislation (See note 11).
11. These terms and conditions shall apply to the requirements set out in Regulation (EU) 2016/425 of the European Parliament and of the council of 9th March 2016 on personal protective equipment or to UK legislation relating to UKCA Marking as defined within the issued certificate.